

ADIX IX-DCKT970



CUT THE CORD THAT

BINDS YOU TO YOUR DESK

IWATSU

**TOOLS THAT EVOLVE FASTER
THAN YOUR BUSINESS**

- ▶▶▶ Is most of your time spent out of the office?
- ▶▶▶ Tired of missing important calls?
- ▶▶▶ Too many voice mail messages to return?

Then the IX-DCKT970 is the solution you've been waiting for.

The IX-DCKT970 digital wireless key telephone emulates the functionality of a corded ADIX Omega-Phone, while enabling you with greater flexibility and improved productivity while away from your desk. From virtually any location in your office, IX-DCKT970 wireless capabilities allow you to answer important calls for increased efficiency and customer satisfaction.

Iwatsu's IX-DCKT970 delivers the following advantages:

Increased Mobility. The IX-DCKT970 has seven times the range of a traditional wireless telephone.

Digital Technology. Provides voice clarity that is indistinguishable from a corded telephone.

LCD Indication. A 2-line/16-digit Liquid Crystal Display (LCD) provides call status and ADIX function information.

Enhanced Security. Super Long Range 900MHz Digital Spread Spectrum offers unparalleled range and provides superior voice communications security.

Easy Installation. The IX-DCKT970 plugs into an ADIX station port and provides a connection for the addition of an ADIX Omega-Phone.

DCKT970 Features

- ▶ **Two-line, 16-digit LCD** – Displays easy-to-read information and status icons.
- ▶ **Four Programmable Keys** – Flexible keys for multiple line and feature access.
- ▶ **Headset Jack** – Hands-free operation when an optional headset is installed.
- ▶ **Memory** – Stores up to 20 phone numbers for convenient speed dialing.
- ▶ **Mute Key** – Allows users to turn off the handset microphone while on a call.
- ▶ **Vibrate Ringer Alert** – Notifies user of an incoming call by vibration versus ringing.
- ▶ **Message Waiting Display** – Illuminates when there is a message waiting.
- ▶ **10 Channels** – Supports up to 10 simultaneous calls.
- ▶ **Low Battery Protection System** – Provides six-hour talk time, four-day standby time.
- ▶ **Wall Mountable Base and Charging Unit** – Separate base unit and drop-in charge unit with convenient wall mounting

Specifications

General:

Frequency Control: Phase Lock Loop
Modulation: Spread Spectrum
Operating Temperature: 0° to 50° C (+32° F to +122° F)

Base Unit:

Receive/Transmit Frequency: 902 MHz to 928 MHz
Power Requirements: 10V DC from supplied AC Adapter
Size: 4 1/4 in. W x 7 1/2 in. D x 2 1/4 in. H
Weight: Approx. 15.4 oz.
Color: Black

Handset:

Receive/Transmit Frequency: 902 MHz to 928 MHz
Power Requirements: Nickel-Cadmium Battery Pack
Size: 2 1/5 in. W x 1 2/3 in. D x 8 2/3 in. H with antenna
Weight: Approx. 8.8 oz. with battery
Battery: Capacity 800 mAh, 3.6V
Talk Time: 6 hours (typical)
Standby Time: 4 days (typical)
Color: Black

IWATSU
TELECOMMUNICATIONS PRODUCTS

1-800-974-5070
www.iwatsu.com

Iwatsu America, Inc.
8001 Jetstar Dr.
Irving, TX 75063